

Product Data And Specifications

Stainless Steel Butterfly Sprinkler

Stainless Steel Butterfly Sprinkler designed for use in home watering systems and agricultural use.

- Hard-Wearing Stainless Steel Frame
- Stainless Steel Spinner, Pin and Screw
- *Maximum operating pressure of 200 kPa*
- *Discharge at 200 kPa is 17 lpm*
- *Triangular spacing maximum of 6 meters*
- *Square spacing maximum of 5 meters*
- *Best results are achieved at 6 meter triangular spacing*



Product Models	Code
15mm female bsp inlet, single stainless spinner, with stainless pin and screw	XMG650MS
15mm female bsp inlet, double stainless spinner, with stainless pin and screw	XMG650M
15mm female bsp inlet, single poly spinner, with stainless pin and screw	XMG650S
15mm female bsp inlet, double poly spinner, with stainless pin and screw	XMG650P
20mm female bsp inlet, single stainless spinner, with stainless pin and screw	XMG675MS
20mm female bsp inlet, double stainless spinner, with stainless pin and screw	XMG675M
20mm female bsp inlet, single poly spinner, with stainless pin and screw	XMG675S
20mm female bsp inlet, double poly spinner, with stainless pin and screw	XMG675P
15mm female bsp inlet, double poly spinner, with stainless pin and screw PP	XMG650PP
15mm female bsp inlet, single poly spinner, with stainless pin and screw PP	XMG650SP
15mm female bsp inlet, single stainless spinner with stainless pin and screw PP	XMG650MSP